



GENERAL NOTES

- 1. ALL FRAMES ARE VIEWED LOOKING AFT.
- 2. ALL FLANGES OF STIFFS OR GRIDDERS ARE TO BE SNIPPED WHEN ENDS CONNECT TO BHDS, DECKS OR SHELL.
- 3. ALL SNIPES TO BE 1/2"x1/2" UNLESS NOTED OTHERWISE.
- 4. ALL VENT DRAIN HOLES TO BE 3" RADII.
- 5. FOR REFERENCE TO STRUCTURAL DETAILS SEE DRAWING S-10.
- 6. MAIN DECK DESIGNED FOR 200LBS/FT<sup>2</sup> LOADING FROM FRAME.
- 7. UNBRACKETED STIFFENERS OF SHELL, WT OR OT BHDS AND HOUSE FRONTS ARE TO HAVE DOUBLE CONTINUOUS WELDS FOR 1/10 OF THEIR LENGTH AT EACH END.
- 8. UNBRACKETED STIFFENERS OF NIGHTIGHT STRUCTURAL BHDS, DK HOUSE SIDES AND AFTER ENDS ARE TO HAVE A PAIR OF MATCHED INTERMITTENT WELDS AT EACH END.
- 9. ALL LIGHTING HOLES ARE CENTERED BETWEEN FRAMES UNLESS NOTED OTHERWISE.

REV.	DESCRIPTION	DATE	BY
	REVISIONS		
	<b>MASTER BOAT BUILDERS, INC.</b>		
	P.O. Box 702 Boyou LaBatre, AL 36509		
	150'-0" x 36'-0" x 12'-0"		
	OSV		
Drawn By: C. BRAUN	Approved By:	Scale: 1/4"=1'-0"	Sheet No: 354
<b>FRAMES 17 THRU 23</b>		Date: 5-29-02	
Sheet: 1 of 1	Drawing Number:	S-2B	Rev: 0