



**GENERAL NOTE**

1. ALL FLANGES OF STIFF OR GIRDERS ARE TO BE SNIPPED WHEN ENDS CONNECT TO BHDS, DISCS OR SHELL.
2. ALL SNIPES TO BE 1 1/2" x 1/2" UNLESS NOTED OTHERWISE.
3. ALL VENT DRAIN HOLES TO BE 5" DIAMETER.
4. FOR REFERENCE TO STRUCTURAL DETAILS SEE DRAWING S-10.
5. MAIN DECK DESIGNED FOR 200LBS/FT<sup>2</sup> LOADING FROM FRAME 24 FWD AND 54LBS/FT<sup>2</sup> FROM FRAME 24 AFT.
6. UNBRACKETED STIFFENERS OF SHELL, WT OR OT BHDS AND HOUSE FRONTS ARE TO HAVE DOUBLE CONTINUOUS WELDS FOR 1/10 OF THEIR LENGTH AT EACH END.
7. UNBRACKETED STIFFENERS OF HONDSIGHT STRUCTURAL BHDS, DK HOUSE SIDES AND AFTER ENDS ARE TO HAVE A PAIR OF MATCHED INTERMITTENT WELDS AT EACH END.

1	CL PROFILE; ADDED BRKTS TO STIFF ON FR 6 & 53, ADDED TRIPPING BRACKET TO FR 45 & CHANGED SIZE OF FLG PLATE @ FR 38-53.	1-8-03	C.B.
2	6'-6" OCL (S); ADDED VERTICAL STIFF TO MOONPOOL BHD & INDICATED TK TOP OUTBD ONLY.	6/24/02	C.B.
REV.	DESCRIPTION	DATE	BY
1	1. ADDED/CORRECTED LOFTED PC MARKS.	6/24/02	C.B.
REVISIONS			
<b>MASTER BOAT BUILDERS, INC.</b>			
P.O. Box 702 Bayou LaBatre, AL 36509			
150'-0" x 36'-0" x 12'-0"			
OSV			
Drawn By :	C. BRAUN	Approved By :	
Scale :	3/16"=1'-0"	Date :	5-28-02
<b>CL PROFILE &amp; LONG'L BHDS</b>			
Sheet :	1 of 2	Drawing Number :	S-4
Contract No. :			2