

Drew Marine Signal and Safety Germany GmbH

Chemwatch: **65-6261** Version No: **3.1.1.1** Safety Data Sheet

SECTION 1 IDENTIFICATION

Product Identifier

Product name	RED PARACHUTE ROCKET	
Synonyms	Comet Parachute Signal Rocket, red – ArtNo.: 9163100, 9163101, 9163103, 9163105, 9163106, 9163107, 9163110, 9163150, Pains Wessex Para Red Rocket MK8A – ArtNo.: 9506370, 9506720, 9506727, 9506850, 9506950, 9506970, Aurora PW Para Red Rocket, ArtNo. 9506960, 9506980, Oroquieta Parachute Signal Rocket, red, Oro2	
Proper shipping name	SIGNALS, DISTRESS, ship†	
Other means of identification	Not Available	

Recommended use of the chemical and restrictions on use

Relevant identified uses	Use according to manufacturer's directions. Sea distress signal. A day or night long-range distress signal. 12 may be carried on ships bridge and there is a requirement for 4 in ships lifeboats and liferafts. Also suitable for use in other commercial and recreational boats.
--------------------------	--

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	Drew Marine Signal and Safety Germany GmbH	
Address	Vieländer Weg 147 Bremerhaven 27574 Germany	
Telephone	49 471 3930	
Fax	+49 471 3932 10	
Website	www.signalandsafety.com	
Email	info@signalandsafety.com	

Emergency phone number

Association / Organisation	Consultant Lutz Harder GmbH	
Emergency telephone numbers	+49 178 433 7434	
Other emergency telephone numbers	CHEMWATCH: From whithin the US and CANADA: 1 877 715 9305 OR call +613 9573 3112. From outside the US and Canada: +800 2436 2255 (+800 CHEMCALL) or +61 3 9573 3112	

SECTION 2 HAZARD(S) IDENTIFICATION

Classification of the substance or mixture

CANADIAN WHMIS SYMBOLS



CANADIAN WHMIS CLASSIFICATION

Ingredient	CAS number	Classification Description	Classification Code
magnesium	7439-95-4	Flammable Solid, Reactive Flammable Material	B4, B6
potassium nitrate	7757-79-1	Oxidizing Material	С
aluminium	7429-90-5	Reactive Flammable Material, Flammable Solid, Toxic Material Causing Other Toxic Effects	B6, B4, D2B
potassium perchlorate	7778-74-7	Oxidizing Material	С
barium chromate	10294-40-3	Very Toxic Material Causing Other Toxic Effects, Toxic Material Causing Other Toxic Effects	D2A, D2B
Classification	Explosive Division 1.4		

Label elements

Issue Date: 05/09/2016

Print Date: 07/09/2016 S.GHS.CAN.EN

GHS label elements	
SIGNAL WORD	WARNING
Hazard statement(s)	
H204	Fire or projection hazard.

Hazard(s) not otherwise specified

Not Applicable

Precautionary statement(s) Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
P234	Keep only in original packaging.	
P250	Do not subject to grinding/shock/sources of friction.	
P280	Wear protective gloves/protective clothing/eye protection/face protection.	
P240	Ground and bond container and receiving equipment.	

Precautionary statement(s) Response

P370+P372+P380+P373	In case of fire: Explosion risk. Evacuate area. DO NOT fight fire when fire reaches explosives.	
P370+P380+P375 In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.		

Precautionary statement(s) Storage

P401

Store in accordance with local regulations for explosives.

Precautionary statement(s) Disposal

P501

Dispose of contents/container in accordance with local regulations.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
		device contains
		lighter composition, delay composition and ignition composition
		polytechnic materials of;
7439-95-4	30-60	magnesium
10042-76-9	30-60	strontium nitrate
7757-79-1	70-80	potassium nitrate
7429-90-5	10-30	aluminium
7778-74-7	5-10	potassium perchlorate
		rocket propellant;
10294-40-3	10-30	barium chromate

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4 FIRST-AID MEASURES

Description of first aid measures

Eye Contact	If this product comes in contact with eyes: Wash out immediately with water. If irritation continues, seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. 	
Skin Contact	Skin Contact If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.	
Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. 	

	 Transport to hospital, or doctor, without delay.
Ingestion	 Not considered a normal route of entry. If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIRE-FIGHTING MEASURES

Extinguishing media

- DANGER: Deliver media remotely.
- For minor fires: Flooding quantities only.
 For large fires: Do not attempt to extinguish.

Apply by mechanical means only.

Special hazards arising from the substrate or mixture

Fire Incompatibility	Avoid contact with other chemicals.
----------------------	-------------------------------------

Special protective equipment and precautions for fire-fighters

Fire Fighting	 WARNING: EXPLOSIVE MATERIALS / ARTICLES PRESENT! Evacuate all personnel and move upwind. Prevent re-entry. Alert Fire Brigade and tell them location and nature of hazard. May detonate and burning material may be propelled from fire. Wear full-body protective clothing with breathing apparatus. Prevent, by any means available, spillage and fire effluent from entering drains and water courses. Fight fire from safe distances and from protected locations. Use flooding quantities of water. DO NOT approach containers or packages suspected to be hot. Cool any exposed containers on tinvolved in fire from a protected location. Equipment should be thoroughly decontaminated after use. Slight hazard when exposed to heat, flame and oxidisers.
Fire/Explosion Hazard	Division 1.4 Substances, mixtures and articles which present no significant hazard: substances, mixtures and articles which present only a small hazard in the event of ignition or initiation. The effects are largely confined to the package and no projection of fragments of appreciable size or range is to be expected. An external fire shall not cause virtually instantaneous explosion of almost the entire contents of the package. Compatibility Group G explosives are pyrotechnic substances, or article containing a pyrotechnic substances, or article containing both an explosive substance and an illuminating, incendiary, tear- or smoke-producing substance (other than a water-activated article or one containing white phosphorus, phosphides, a pyrophoric substance, a flammable liquid or gel, or hypergolic liquids). Combustible. Will burn if ignited.Combustion products include; carbon monoxide (CO) carbon dioxide (CO2) other pyrolysis products typical of burning organic material

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	WARNING:: EXPLOSIVE. BLAST and/or PROJECTION and/or FIRE HAZARD Clean up all spills immediately. Avoid inhalation of the material and avoid contact with eyes and skin. Wear impervious gloves and safety glasses. Remove all ignition sources. Use spark-free tools when handling. Sweep into non-sparking containers or barrels and moisten with water. Place spilled material in clean, sealable, labelled container for disposal. Flush area with large amounts of water.
Major Spills	 WARNING! EXPLOSIVE. Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear full body protective clothing with breathing apparatus. Consider evacuation (or protect in place). In case of transport accident notify Police, Emergency Authority, Competent Explosives Authority or Manufacturer. No smoking, naked lights, heat or ignition sources. Increase ventilation. Use extreme caution to prevent physical shock. Use ently spark-free shovels and explosion-proof equipment. Collect recoverable material and segregate from spilled material. Wash spill area with large quantities of water.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling ▶ Handle gently. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Avoid all personal contact, including inhalation. Avoid smoking, naked lights, heat or ignition sources. Explosives must not be struck with metal implements. Avoid mechanical and thermal shock and friction. Safe handling Use in a well ventilated area. Avoid contact with incompatible materials. When handling DO NOT eat, drink or smoke. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. ▶ Store cases in a well ventilated magazine licenced for the appropriate Class, Division and Compatibility Group. Rotate stock to prevent ageing. Use on FIFO (first in-first out) basis. Observe manufacturer's storage and handling recommendations contained within this SDS. Store in a cool place in original containers. Keep containers securely sealed. No smoking, naked lights, heat or ignition sources. Store in an isolated area away from other materials. Other information Keep storage area free of debris, waste and combustibles. Protect containers against physical damage. Check regularly for spills and leaks NOTE: If explosives need to be destroyed contact the Competent Authority. Store away from incompatible materials. Keep out of reach of children.

Conditions for safe storage, including any incompatibilities

Suitable container	 All packaging for Class 1 Goods shall be in accordance with the requirements of the relevant Code for the transport of Dangerous Goods. Class 1 is unique in that the type of packaging used frequently has a very decisive effect on the hazard and therefore on the assignment to a particular division
Storage incompatibility	 Avoid contact with other explosives, pyrotechnics, solvents, adhesives, paints, cleaners and unauthorized metals, plastics, packing equipment and materials. Avoid contamination with acids, alkalis, reducing agents, amines and phosphorus. Explosion hazard may follow contact with incompatible materials

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	magnesium	Particles (Insoluble or Poorly Soluble) Not Otherwise Specified: Inhalable fraction++ / Particles (Insoluble or Poorly Soluble) Not Otherwise Specified: Respirable fraction++	10 mg/m3 / 3 mg/m3	20 mg/m3 / 6 mg/m3	Not Available	Not Available
Canada - (English)	magnesium	Particles (Insoluble or Poorly Soluble) Not Otherwise Specified: Inhalable fraction / Particles (Insoluble or Poorly Soluble) Not Otherwise Specified: Respirable fraction	10 mg/m3 / 3 mg/m3	20 mg/m3 / 6 mg/m3	Not Available	Not Available
Canada - Nova Scotia Occupational Exposure Limits	magnesium	Particles (Insoluble or Poorly Soluble) [NOS] Inhalable particles / Particles (Insoluble or Poorly Soluble) [NOS] Respirable particles	10 mg/m3 / 3 mg/m3	Not Available	Not Available	See Appendix B current TLV/BEI Book
Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)	magnesium	Particulates Not Otherwise Classified (PNOC)	10 mg/m3	Not Available	Not Available	Not Available
Canada - Alberta Occupational Exposure Limits	magnesium	Particulate Not Otherwise Regulated - Total / Particulate Not Otherwise Regulated - Respirable	10 mg/m3 / 3 mg/m3	Not Available	Not Available	Not Available
Canada - British Columbia Occupational Exposure Limits	magnesium	Particles (Insoluble or Poorly Soluble) Not Otherwise Classified (PNOC)	10 mg/m3	Not Available	Not Available	(N) - the 8-hour TWA listed in the Table is for the total dust. The substance also has an 8-hour TWA of 3 mg/m3 for the respirable fraction.
Canada - Ontario Occupational Exposure Limits	magnesium	Particles (Insoluble or Poorly Soluble) Not Otherwise Specified (PNOS)	10, 3 mg/m3	Not Available	Not Available	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	aluminium	Particles (Insoluble or Poorly Soluble) Not Otherwise Specified: Inhalable fraction++ / Particles (Insoluble or Poorly Soluble) Not Otherwise Specified: Respirable fraction++	10 mg/m3 / 3 mg/m3	20 mg/m3 / 6 mg/m3	Not Available	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	aluminium	Aluminum and compounds (as Al): Pyro powders	5 mg/m3	10 mg/m3	Not Available	Not Available

Canada - (English)	aluminium	Particles (Insoluble or Poorly Soluble) Not Otherwise Specified: Inhalable fraction / Particles (Insoluble or Poorly Soluble) Not Otherwise Specified: Respirable fraction	10 mg/m3 / 3 mg/m3	20 mg/m3 / 6 mg/m3	Not Available	Not Available
Canada - (English)	aluminium	Aluminum and compounds (as Al): Pyro powders	5 mg/m3	10 mg/m3	Not Available	Not Available
Canada - Nova Scotia Occupational Exposure Limits	aluminium	Aluminum - Metal	1 mg/m3	Not Available	Not Available	TLV Basis: Pneumoconiosis; lower respiratory tract irritation; neurotoxicity
Canada - Prince Edward Island Occupational Exposure Limits	aluminium	Aluminum metal and insoluble compounds	1 mg/m3	Not Available	Not Available	TLV® Basis: Pneumoconiosis; LRT irr; neurotoxicity
Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)	aluminium	Aluminum (as Al) / Aluminum (as Al): Metal / Aluminum (as Al): Welding fumes	10 mg/m3 / 5 mg/m3	Not Available	Not Available	Not Available
Canada - Manitoba Occupational Exposure Limits	aluminium	Not Available	1 mg/m3	Not Available	Not Available	Not Available
Canada - Alberta Occupational Exposure Limits	aluminium	Aluminum - Metal Dust	10 mg/m3	Not Available	Not Available	Not Available
Canada - British Columbia Occupational Exposure Limits	aluminium	Aluminum metal and insoluble compounds, Respirable	1.0 mg/m3	Not Available	Not Available	Not Available
Canada - British Columbia Occupational Exposure Limits	aluminium	Particles (Insoluble or Poorly Soluble) Not Otherwise Classified (PNOC)	10 mg/m3	Not Available	Not Available	(N) - the 8-hour TWA listed in the Table is for the total dust. The substance also has an 8-hour TWA of 3 mg/m3 for the respirable fraction.
Canada - Ontario Occupational Exposure Limits	aluminium	Particles (Insoluble or Poorly Soluble) Not Otherwise Specified (PNOS)	10, 3 mg/m3	Not Available	Not Available	Not Available
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	barium chromate	Chromium - Metal and insoluble salts	0.1 mg/m3 / ppm	3.0 mg/m3 / ppm	Not Available	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	barium chromate	Chromium metal and inorganic compounds, (as Cr): Insoluble Cr (VI) compounds	0.01 mg/m3	0.03 mg/m3	Not Available	T20
Canada - Saskatchewan Occupational Health and Safety Regulations - Designated Chemical Substances	barium chromate	Chromium compounds, hexavalent	Not Available	Not Available	Not Available	Not Available
Canada - Nova Scotia Occupational Exposure Limits	barium chromate	Barium chromate	0.01 mg/m3	Not Available	Not Available	TLV Basis: lung cancer. Measured as Cr.
Canada - Prince Edward Island Occupational Exposure Limits	barium chromate	Chromium, and inorganic compounds, as Cr - Insoluble Cr VI compounds	0.01 mg/m3	Not Available	Not Available	TLV® Basis: Lung cancer
Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)	barium chromate	Chromite ore processing (chromate) (as Cr)	0.05 mg/m3	Not Available	Not Available	Not Available
Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)	barium chromate	Chromium VI, water insoluble inorganic compounds (as Cr)	0.01 mg/m3	Not Available	Not Available	Not Available
Canada - Manitoba Occupational Exposure Limits	barium chromate	Not Available	0.01 mg/m3	Not Available	Not Available	Not Available
Canada - Alberta Occupational Exposure Limits	barium chromate	Chromite ore processing (Chromate), as Cr	0.05 mg/m3	Not Available	Not Available	Not Available
Canada - Alberta Occupational Exposure Limits	barium chromate	Chromium, metal and inorganic compounds, as Cr: Insoluble Cr VI compounds	0.01 mg/m3	Not Available	Not Available	Not Available
Canada - British Columbia Occupational Exposure Limits	barium chromate	Chromite ore processing (Chromate), as Cr	0.05 mg/m3	Not Available	Not Available	Not Available
Canada - British Columbia Occupational Exposure Limits	barium chromate	Chromium (VI) inorganic compounds - Insoluble, as Cr	0.01 mg/m3	Not Available	Not Available	Not Available

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEI	EL-2	TEEL-3
magnesium	Magnesium	0.016 mg/m3	0.17	7 mg/m3	1 mg/m3
strontium nitrate	Strontium nitrate	0.2 mg/m3	2.2	mg/m3	370 mg/m3
potassium nitrate	Potassium nitrate	0.074 mg/m3	0.82	2 mg/m3	600 mg/m3
aluminium	Aluminum	3 mg/m3	33 r	mg/m3	200 mg/m3
potassium perchlorate	Potassium perchlorate	23 mg/m3	250) mg/m3	1500 mg/m3
barium chromate	Barium chromate	0.15 mg/m3	25 r	mg/m3	150 mg/m3
Ingredient	Original IDLH		Revised IDLH		
magnesium	Not Available		Not Available		
strontium nitrate	Not Available		Not Available		

potassium nitrate	Not Available	Not Available
aluminium	Not Available	Not Available
potassium perchlorate	Not Available	Not Available
barium chromate	Not Available	Not Available

Exposure controls

Appropriate engineering controls	Engineering controls for explosive articles are designed to reduce or eliminate fragmentation and/or blast effects either by suppression of the source of detonation or by protection at the exposed location, or both. Barricades, shields, contained detonation chambers, and "zero quantity-distance (Q-D)" magazines are examples of engineering controls. Engineering controls are designed and tested in a rigorous fashion. The construction of the engineering control must be carefully duplicated in field applications to assure it will function properly. It is thus imperative that engineering controls be built exactly in accordance with the design package, and that they be used only for the articles (e.g.munitions) for which they are authorised.
Personal protection	
Eye and face protection	 Safety glasses with side shields Chemical goggles
Skin protection	See Hand protection below
Hands/feet protection	 Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber
Body protection	See Other protection below
Other protection	 Fire resistant/ heat resistant gloves where practical, otherwise Heavy-duty chemically resistant gloves capable of providing short-term protection against spontaneous ignition. Safety footwear Hard hat [Ear Protection.
Thermal hazards	Not Available

Respiratory protection

Respiratory protection not normally required due to the physical form of the product.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Steel tube with orange/yellow plastic outer casing pressed w	ith black/grey polytechnical ingredier	ts.
Physical state	Manufactured	Relative density (Water = 1)	Not Applicable
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	>160
pH (as supplied)	Not Applicable	Decomposition temperature	Not Applicable
Melting point / freezing point (°C)	Not Applicable	Viscosity (cSt)	Not Applicable
Initial boiling point and boiling range (°C)	Not Applicable	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	160	Taste	Not Available
Evaporation rate	Not Applicable	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	Not Applicable
Vapour pressure (kPa)	Not Applicable	Gas group	Not Available
Solubility in water (g/L)	Immiscible	pH as a solution (1%)	Not Applicable
Vapour density (Air = 1)	Not Applicable	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	 Presence of shock and friction Presence of heat source and ignition source Product is considered stable under normal handling conditions. Stable under normal storage conditions. Hazardous polymerization will not occur.

	Avoid contact with other chemicals.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	Not normally a hazard due to physical form of product. Inhalation of vapour is more likely at higher than normal temperature The vapour is discomforting	25.	
Ingestion	Not normally a hazard due to physical form of product. Considered an unlikely route of entry in commercial/industrial enviro	nments	
Skin Contact	Not normally a hazard due to physical form of product. The vapour is discomforting		
Eye	Not normally a hazard due to physical form of product. The vapour is discomforting		
Chronic	 Generally not applicable. 		
RED PARACHUTE	тохісіту	IRRITATION	
ROCKET	Not Available	Not Available	
	ΤΟΧΙΟΙΤΥ	IRRITATION	
magnesium	Oral (rat) LD50: >2000 mg/kg ^[1]	Nil reported [Manufacturer]	
	тохісіту	IRRITATION	
strontium nitrate	Oral (rat) LD50: 1892 mg/kg ^[2]	Nil reported	
	ΤΟΧΙΟΙΤΥ	IRRITATION	
potassium nitrate	dermal (rat) LD50: >5000 mg/kg ^[1]	Nil reported	
	Oral (rat) LD50: >2000 mg/kg ^[1]		
	ΤΟΧΙΟΙΤΥ	IRRITATION	
aluminium	Oral (rat) LD50: >2000 mg/kg ^[1]	Not Available	
	ΤΟΧΙΟΙΤΥ	IRRITATION	
potassium perchlorate	Not Available	Not Available	
	ΤΟΧΙΟΙΤΥ	IRRITATION	
barium chromate	Oral (rat) LD50: >2000 mg/kg ^[2]	[CCINFO - Dominion Colour]	
		Nil reported	
Legend:	1. Value obtained from Europe ECHA Registered Substances - Act	Ite toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specifi	ied da

STRONTIUM NITRATE	Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.
BARIUM CHROMATE	The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested. WARNING: This substance has been classified by the IARC as Group 1: CARCINOGENIC TO HUMANS.
ALUMINIUM & POTASSIUM PERCHLORATE	No significant acute toxicological data identified in literature search.

Acute Toxicity	0	Carcinogenicity	0
Skin Irritation/Corrosion	0	Reproductivity	0
Serious Eye Damage/Irritation	0	STOT - Single Exposure	0
Respiratory or Skin sensitisation	0	STOT - Repeated Exposure	0
Mutagenicity	0	Aspiration Hazard	0
		Legend: 🗙	– Data available but does not fill the criteria for classification

Data required to make classification available

S − Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Ingredient	Endpoint	Test Duration (hr)	Species	Value	Source
magnesium	LC50	96	Fish	541mg/L	2
magnesium	EC50	48	Crustacea	344mg/L	2
magnesium	EC50	72	Algae or other aquatic plants	>12mg/L	2
nagnesium	EC50	72	Algae or other aquatic plants	>12mg/L	2
nagnesium	NOEC	72	Algae or other aquatic plants	>=12mg/L	2
strontium nitrate	LC50	96	Fish	>40.3mg/L	2
strontium nitrate	EC50	48	Crustacea	94mg/L	2
strontium nitrate	EC50	72	Algae or other aquatic plants	>43.3mg/L	2
strontium nitrate	EC50	72	Algae or other aquatic plants	>43.3mg/L	2
strontium nitrate	NOEC	480	Algae or other aquatic plants	15mg/L	2
potassium nitrate	LC50	96	Fish	22.5mg/L	4
potassium nitrate	EC50	48	Crustacea	490mg/L	2
potassium nitrate	EC50	96	Algae or other aquatic plants	1181.887mg/L	3
potassium nitrate	EC50	96	Crustacea	39mg/L	2
ootassium nitrate	NOEC	96	Fish	98.9mg/L	2
aluminium	LC50	96	Fish	0.078-0.108mg/L	2
aluminium	EC50	48	Crustacea	0.7364mg/L	2
aluminium	EC50	96	Algae or other aquatic plants	0.0054mg/L	2
aluminium	BCF	360	Algae or other aquatic plants	9mg/L	4
aluminium	EC50	120	Fish	0.000051mg/L	5
aluminium	NOEC	72	Algae or other aquatic plants	>=0.004mg/L	2
potassium perchlorate	EC10	24	Algae or other aquatic plants	>1000mg/L	4

Legend:

Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) -Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
potassium nitrate	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation		
potassium nitrate	LOW (LogKOW = 0.209)		
Mobility in soil			
Mobility in soil Ingredient	Mobility		

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal	 Explosives must not be thrown away, buried, discarded or placed with garbage. Explosives which are surplus, deteriorated or considered unsafe for transport, storage or use shall be destroyed and the statutory authorities shall be notified. This material may be disposed of by burning or detonation but the operation may only be performed under the control of a person trained in the safe destruction of explosives. Refer to local Waste Disposal Authority and supplier for suitable disposal procedure.
---------------------------------	---

SECTION 14 TRANSPORT INFORMATION

Labels Required



Land transport (TDG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR)

UN number	0505			
UN proper shipping name	Signals, distress ship			
Transport hazard class(es)	ICAO/IATA Class 1.4G ICAO / IATA Subrisk Not Applicable ERG Code 1L			
Packing group	Not Applicable	Not Applicable		
Environmental hazard	Not Applicable			
	Special provisions	Not Applicable		
	Cargo Only Packing Instructions	135		
	Cargo Only Maximum Qty / Pack	75 kg		
Special precautions for user	Passenger and Cargo Packing Instructions	Forbidden		
	Passenger and Cargo Maximum Qty / Pack	Forbidden		
	Passenger and Cargo Limited Quantity Packing Instructions	Forbidden		
	Passenger and Cargo Limited Maximum Qty / Pack	Forbidden		

Sea transport (IMDG-Code / GGVSee)

	<u>.</u>		
UN number	0505		
UN proper shipping name	SIGNALS, DISTRESS ship		
Transport hazard class(es)	IMDG Class 1.4G IMDG Subrisk Not Applicable		
Packing group	Not Applicable		
Environmental hazard	Not Applicable		
Special precautions for user	EMS Number F-B, S-X Special provisions Not Applicable Limited Quantities 0		

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

MAGNESIUM(7439-95-4) IS FOUND ON THE FOLLOWING REGULATORY LISTS	
Canada - (English)	Canada - Quebec Permissible Exposure Values for Airborne Contaminants (French)
Canada - Alberta Occupational Exposure Limits	Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits
Canada - British Columbia Occupational Exposure Limits	Canada Categorization decisions for all DSL substances
Canada - Nova Scotia Occupational Exposure Limits	Canada Domestic Substances List (DSL)
Canada - Ontario Occupational Exposure Limits	International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs
	Monographs
STRONTIUM NITRATE(10042-76-9) IS FOUND ON THE FOLLOWING REGULATORY LISTS	
Canada Categorization decisions for all DSL substances	Canada Domestic Substances List (DSL)
POTASSIUM NITRATE(7757-79-1) IS FOUND ON THE FOLLOWING REGULATORY LISTS	
Canada Categorization decisions for all DSL substances	Canada Domestic Substances List (DSL)
ALUMINIUM(7429-90-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS	

Canada - (English) Canada - Quebec Permissible Exposure Values for Airborne Contaminants (French) Canada - Alberta Occupational Exposure Limits Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits Canada - British Columbia Occupational Exposure Limits Canada Categorization decisions for all DSL substances Canada - Nova Scotia Occupational Exposure Limits Canada Domestic Substances List (DSL) International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Canada - Ontario Occupational Exposure Limits Canada - Prince Edward Island Occupational Exposure Limits Monographs POTASSIUM PERCHLORATE(7778-74-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS Canada Categorization decisions for all DSL substances Canada Domestic Substances List (DSL) BARIUM CHROMATE(10294-40-3) IS FOUND ON THE FOLLOWING REGULATORY LISTS Canada - Alberta Occupational Exposure Limits Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits Canada - British Columbia Occupational Exposure Limits Canada - Saskatchewan Occupational Health and Safety Regulations - Designated Chemical Substances Canada - Nova Scotia Occupational Exposure Limits Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances Canada - Prince Edward Island Occupational Exposure Limits Canada Categorization decisions for all DSL substances Canada - Prince Edward Island Occupational Exposure Limits - Carcinogens Canada Domestic Substances List (DSL) Canada - Quebec Permissible Exposure Values for Airborne Contaminants (French) International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs National Inventory Status Australia - AICS Y

Canada - DSL	Y
Canada - NDSL	N (barium chromate; strontium nitrate; magnesium; aluminium; potassium perchlorate; potassium nitrate)
China - IECSC	Y
Europe - EINEC / ELINCS / NLP	Υ
Japan - ENCS	N (magnesium; aluminium)
Korea - KECI	Y
New Zealand - NZIoC	Y
Philippines - PICCS	Y
USA - TSCA	Y
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Other information

Ingredients with multiple cas numbers

Name	CAS No
strontium nitrate	10042-76-9, 13470-05-8
aluminium	7429-90-5, 91728-14-2

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.